

## 2.4 GHz Rubber Duck Antenna CSG 62409 RDN

PARAMETERS	SPECIFICATIONS
Frequency Range	2400~2500 MHz
Gain	9.0 dBi
VSWR	≤1.5: 1
H/E-Plane BW	360°
Polarization	Vertical
Max. Power	25 Watts
Impedance	50 Ω
Connector	SMA/ TNC or RP SMA/TNC-male
Color	Black
Weight (Approx.)	0.75 Kg
Working Temperature	-40°C - +60°C



## 2.4 GHz Rubber Duck Antenna CSG 62405 RDN

PARAMETERS	SPECIFICATIONS
Frequency Range	2400~2500 MHz
Gain	5.0 dBi
VSWR	≤1.5: 1
H/E-Plane BW	360°
Polarization	Vertical
Max. Power	25 / 50 Watts
Impedance	50 Ω
Connector	SMA Male, SMA Right Angle Male
Color	Black
Height (Approx.)	187 mm, 189 mm
Weight (Approx.)	0.75 Kg
Working Temperature	-40°C - +60°C



**Note:** Mounting Hardware and Brackets are supplied with Antenna

**WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT**

## 2.4 GHz Rubber Duck Antenna CSG 62402 RDN

PARAMETERS	SPECIFICATIONS
Frequency Range	2400~2500 MHz
Gain	2.0 dBi
VSWR	≤1.5: 1
H/E-Plane BW	360°
Polarization	Vertical
Max. Power	25 Watts
Impedance	50 Ω
Connector	RPSMA / RPTNC Male
Color	Black
Height (Approx.)	83 mm
Weight (Approx.)	0.03 Kg
Working Temperature	-40°C - +60°C



**Note:** Mounting Hardware and Brackets are supplied with Antenna

**WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT**